


Getalit[®] Care instructions

For doors with HPL finish

Getalit HPL. A success story stretching back decades and a material composition with a real future! Continuous further development – both in terms of the decor and the surface finishes – create a contemporary product. Resin-saturated kraft papers, printed or coloured decor papers and a transparent overlayer protection are pressed together during the manufacturing process. This results in a highly resistant material that can be used in numerous different ways.

Structure of the Getalit finish



Getalit surface properties



scratch
resistant



food safe



lightfast



abrasion
resistant



heat resis-
tant



stainproof



impact
resistant



steam
resistant

Care

Is your HPL PVC-foiled door looking a little dirty? First try to clean it with a damp cleaning cloth. If necessary, you can also use clean water and/or a non-abrasive household cleaner to remove the dirt. To remove particularly stubborn stains or marks – such as tar, wax crayons or water-resistant felt pens – use pure alcohol. Apply the alcohol with a soft, clean cloth. Avoid using wax, polish and abrasive materials.

General recommendations

In smoking areas, you can prevent yellow nicotine staining on individual elements (edges, seals, architraves, etc.) by cleaning the doors regularly. We recommend cleaning laminate surfaces once every three months. Adhesive tapes, such as those used when renovating or painting, should be removed again as soon as possible. If adhered for a longer period of time, the adhesive may damage the decor.